


# Our Point , Your Sale

Series	Model Number	Spec.	Pictures	Package Size(cm)
<b>AnyPos 600</b>	<b>AP653</b>	CPU: Baytrail J1800 DualCore,2.41GHz		47*38*56/7kg
		Memory:2GB DDRIII,up to 4GB		
		Ethernet:1*10/100M/1000M		
		HD: 32GB SSD		
		LCD:15" TFT(LG93 1024*768)		
		5 Wire resistive screen		
		color:Black		
		Power: +12V DC adaptor		
		Interfaces:1*12V DC OUT,4*USB+1*Side USB,4*RS232, 1*LPT, 1*KB/MS, 1*Cash Drawer,1*VGA, 2*Audio Jack		
<b>Options</b>				
	OS	POSReady7, Industry Pro Retail 8.1		
MSR	3 tracks	Standard :ISO 7811 / 2, Interface Type :RS232 and USB , Lifetime of Header :500,000 passes min		
Wi-Fi	802.11g/b/n Wireless	High-speed transfer data rate - up to 54Mbps, Indoor: 200m (max); Outdoor: 850m(max) (According to the surrounding condition)		
Cutomer Display	CD220	Display Type:5*7 Dot Matrix Type VFD, 20 columns x 2lines, Character: 10 International Fonts		
	DL150	LCD Size:15" TFT, LCD Resolution: 1024*768, Brightness: ≥250cd/m2, Display Area: 304*228(mm), 5 - wire resistive touch screen optional		
	DL097	LCD Size:9.7" TFT, LCD Resolution: 1024*768, Brightness: ≥250cd/m2, Display Area: 196.6*147.5(mm), Projective Capacitive touch screen optional		
	DL121	LCD Size:12.1" TFT, LCD Resolution: 800*600, Brightness: ≥250cd/m2, Display Area: 245.8*184.3(mm), Projective Capacitive touch screen optional		
Finger print reader	U.are.U® 4500 Module	Pixel resolution: 512 dpi (average x, y over the scan area), Scan capture area: 14.6 mm (nom. width at center) 18.1 mm (nom. length), 8-bit grayscale (256 levels of gray), USB 2.0 Compatible		
iButton	Dallas	Reader and 2 keys		

**Wintec Point of Sale Systems, Ltd**  
**39 Greville Street London EC1N8PJ**  
**Tel: +44(0)2072426146**  
**Mobile: +44(0)7833896022**  
**WWW.WINTECPOS.COM**  
**Sales@wintecpos.com**